

## § 415.224

limitations for Chromium(T) and Nickel(T) are the same as specified in § 415.222(c).

## § 415.224 [Reserved]

## § 415.225 New source performance standards (NSPS).

(a) Any new source subject to this subpart producing titanium dioxide by the sulfate process must achieve the following new source performance standards (NSPS):

### SUBPART V—TITANIUM DIOXIDE-SULFATE PROCESS

Pollutant or pollutant property	NSPS effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (or pounds per 1,000 lb) of product	
TSS .....	110	30
Iron (T) .....	4.1	1.2
Chromium (T) .....	0.27	0.14
Nickel (T) .....	0.18	0.095
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

(b) Any new source subject to this subpart producing titanium dioxide by the chloride process must achieve the following new source performance standards (NSPS):

### SUBPART V—TITANIUM DIOXIDE-CHLORIDE PROCESS

Pollutant or pollutant property	NSPS effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (or pounds per 1,000 lb) of product	
TSS .....	14	4.0
Iron (T) .....	0.52	0.16
Chromium (T) .....	0.023	0.012
ph .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

(c) Any new source subject to this subpart producing titanium dioxide by the simultaneous beneficiation-chlorination (chloride-ilmenite) process must achieve the following new source performance standards (NSPS):

## 40 CFR Ch. I (7–1–09 Edition)

### SUBPART V—TITANIUM DIOXIDE-CHLORIDE-ILMENITE PROCESS

Pollutant or pollutant property	NSPS effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Kg/kg (or pounds per 1,000 lb) of product	
TSS .....	8.4	2.4
Iron (T) .....	0.32	0.096
Chromium (T) .....	0.014	0.0072
Nickel (T) .....	0.020	0.010
pH .....	( <sup>1</sup> )	( <sup>1</sup> )

<sup>1</sup> Within the range 6.0 to 9.0.

## § 415.226 Pretreatment standards for new sources (PSNS).

(a) Except as provided in 40 CFR 403.7, any new source subject to this subpart and producing titanium dioxide by the sulfate process which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS):

### SUBPART V—TITANIUM DIOXIDE—SULFATE PROCESS

Pollutant or pollutant property	PSNS effluent limitations	
	Maximum for any 1 day	Average of daily values for 30 consecutive days
	Milligrams per liter (mg/l)	
Iron (T) .....	8.5	2.5
Chromium (T) .....	0.57	0.30
Nickel (T) .....	0.38	0.20

In cases where POTWs find it necessary to impose mass limitations, the following equivalent mass limitations are provided as an alternate: The limitations for Iron(T), Chromium(T), and Nickel(T) are the same as specified in § 415.225(a).

(b) Except as provided in 40 CFR 403.7, any new source subject to this subpart and producing titanium dioxide by the chloride process which introduces pollutants into a publicly owned treatment works must comply with 40 CFR part 403 and achieve the following pretreatment standards for new sources (PSNS):